



CERTIFICATO DI COLLAUDO

INSPECTION CERTIFICATE

SECTION 1 ACCORDING TO EN 10204 - 2.2

SECTION 2 ACCORDING TO EN 10204 - 3.1

DATA STAMPA: Stamping Date	7/12/18	CERTIFICATO N°: Certificate number	122413	VERGELLA: Wire rod	AT-SG3	COLATA: Charge	18224	CLIENTE / CUSTOMER PAWLOWSKI GMBH	051362
DDT N°		Vs.Rif.Ord. / Your ref. Nr.		Ns.Rif.Ord. Our ref. Nr.		Quantità (KG) Quantity (KG)		OGGENHAUSER HAUPTSTRASSE,77	
18 BO 004627 14,00		YOUR ORDER 125021 DATED 28/09/2018		18 OC 4337 8,00		1.152,000		89522 HEIDENHEIM OGGENHAUSEN	D

CARATTERISTICHE MECCANICHE TIPICHE DEL DEPOSITO / TYPICAL MECHANICAL PROPERTIES OF ALL-WELD METAL

SECTION 1

Rm N/mm ² Tensile Strength MPa	590	Rs N/mm ² Yeld Strength MPa	500	Al % 5d Elongation Percent	26	KV (J) Impact Test	80(-40°C)	Hardness (HRC)	
--	------------	---	------------	-------------------------------	-----------	-----------------------	------------------	----------------	--

ANALISI CHIMICA COLATA / CHEMICAL ANALYSIS (HEAT)

SECTION 2

C %:	0,074	Si %:	0,945	Mn %:	1,625	P %:	0,007	S %:	0,017	Cr %:	0,026	Mo %:	0,006
Ni %:	0,037	V %:	0,003	W %:		Ti %:	0,0090	Al %:	0,002	Zr %:	0,0001	Sn %:	0,0040
Nb %:		Sb %:		As %:	0,0019	N ppm:	36	O ppm:		Cu* %:	0,161	Fx =	

* = incluso rivestimento / coating included

Fx = (10P + 5 Sb + 4 Sn + As) / 100 (elements in ppm)

CARATTERISTICHE FINALI DEL PRODOTTO / FINAL CHARACTERISTICS OF THE PRODUCT

TIPO: Type	AT-SG3	DIAMETRO (mm):	D.0,80	RIVESTIMENTO: Coating	X	Ramato / Coppered Bronzato / Bronzed Extra / Non ramato / Uncoppered
---------------	---------------	-------------------	---------------	--------------------------	----------	--

MIG/TIG: **M**

CLASSIFICAZIONI: SFA-AWS A5.18 ER70S-6
Classifications EN ISO 14341-A- G 46 4 C1/M21 4Si1

Articolo Cliente:
Customer Code:

Member of CISQ Federation

Certified Quality System
According to **UNI EN ISO 9001:2015**
Certificate n° 300/96/S

ITALFIL S.p.A.
Quality Assurance Manager

R.A.Q. R.C.Q.
P.I. DALLA VECCHIA ANDREA
Andrea Dalla Vecchia



0045

06

DoP n° DM010

DIN EN 13479 + DIN EN ISO 14341

To be used for fusion welding of metallic
structures or composite metal and
concrete structures in construction works